NATIONAL FLOORING PRODUCTS

EST ESTATE COLLECTION

RE REG EMB LAMINATE LAM

REG. EMBOSS

Estate Collection
[Registered Embossed | Laminate | 13.5MM]

#819 RE-TL, #820 RE-TL, #821 RE-TL, #822 RE-TL, #823 RE-TL
#824 RE-TL, #825 RE-TL, #826 RE-TL, #827 RE-TL, #828 RE-TL
#829 RE-TL

LIMITED WARRANTY

Finish: Limited Lifetime
Structural: 10 year Commercial

SERIES INFORMATION:

Colors:	Species	Thickness	Width	Length	Wear Layer	SF/BOX	BX/PLT	SF/PLT	BX/WGT	SF/WGT	Waste %
#819 RE-TL-#824 RE-TL	Oak	13.5MM	6 1/2"	2'-6'	AC4	26.08	42	1095	63	2.42 lbs	4-6%
#825 RE-TL-#829 RE-TL	Oak	13.5MM	6 1/2"	48"	AC4	14.86	78	1159	35	2.38 lbs	4-6%

INSTALLATION

- ⊗ Nail
- ⊗ Nail/Glue Assist
- ⊗ Glue Only
- ✓ Float
- ✓ Click
- ✓ Below Grade
- ✓ Radiant Heat

ADDITIONAL INFORMATION:

Core Construction	Tuffcore HDF - High Density Fiberboard
Core Type	Black Core 950 Psi+
Joint System	Unilin - Drop-n-Lock
Texture	Registered Embossed (EIR)
Edge Profile	1.2 mm Painted Bevel
Finish Type	AC4 Melemaine wear layer infused with alluminum oxide
Gloss Levels	5 - 7%
Maintenance	ZEP Hardwood and Laminate Floor Cleaner
Repair Finish	N/A
Expansion Requirements	5/16" expansion gap for the first 20 Lineal feet (length or width). Add additional 1/16" for every 5' of install (length or width) upto 5/8". T-molds are required for rooms exceeding 50 lineal feet in length and width and 40 lineal feet for installations over in floor radiant heat.
Uses	Residential - Commercial

COMPLIANCE:

This series has been tested and contains the following certifications:

CARB Phase II Compliant · floor score · SCScertified · FSC · United States Environmental Protection Agency

COMMON QUESTIONS:

SUBSTATE REQUIREMENTS

Structurally sound, well bounded, flat to within 3/16" in 10' radius or 1/8" in 6' radius, vertical deflection cannot exceed 1/4" in 10' Radius, or more than 1/16" between the floor joist.

APPROVED SUBSTRATES

Underlayment APA grade CDX plywood/OSB, 3000 PSI concrete or 2500 PSI gypcrete. Underlayment grade MDF. See installation guide for additional approved substrates.

WOOD SUBFLOOR (EMC) MOISTURE CONTENT REQUIREMENTS

Should not exceed 12% MC (moisture content).

CONCRETE AND GYPCRETE MOISTURE EMISSIONS, RH, AND PH REQUIREMENTS

Properly install a minimum of 6mil plastic over the entire sub-strate. Overlap all seams 12" and tape all seams with moisture proof tape.

JOBSITE CONDITION RANGES

RH between 30-60% and room temperature between 60 to 80°F. Post installation temperature range must be within 60 to 142 °F.

ACCLIMATION TIMEFRAME

No acclimation is required if the product was stored and/ or transported in 60 to 80°F for at least 24 hours prior to installation. Otherwise, it must acclimate for a minimum of 24 hours. Please see installation guide for radiant heat application.

CAN WE INSTALL A CUSHION UNDERNEATH THE FLOOR?

This product has an attached 1.5mm thick high density EVA cushion. An additional cushion is not compatible.

RUG COMPATIBILITY

Must be breathable, non abrasive, natural fiber rugs. Please see RugPadUSA.com. For example; Anchor Grip, Nature's Grip, RugPro, or Super Lock Natural.

877.238.3225 | www.my-nfp.com

NATIONAL FLOORING PRODUCTS

Note: For accuracy, we used actual material to create these product images. Please be aware that colors on printed media or displayed on a screen may vary from the actual product.

EST ESTATE COLLECTION

Estate Collection
[Registered Embossed | Laminate 13.5MM]

RE REG EMB LAM LAMINATE

REG. EMBOSS

Color # 819 RE-TL Oak

Color # 820 RE-TL Oak

Color # 821 RE-TL Oak

Color # 822 RE-TL Oak

Color # 823 RE-TL Oak

Color # 824 RE-TL Oak

Color # 825 RE-TL Oak

Color # 826 RE-TL Oak

Color # 827 RE-TL Oak

Color # 828 RE-TL Oak

Color # 829 RE-TL Oak